



SuperSlide

Biodegradable Soy-based Release Oil

DESCRIPTION SuperSlide is readily biodegradable soy-based release oil formulated with select US grown vegetable seed oils for use as a high performance release agent.

APPLICATIONS

- Recommended for all types of forming and release applications.
- Highly effective on fiberglass sheetpile/seawalls and marine pilings.

BENEFITS

- Superior releasing properties increase productivity
- Pleasant smelling for good operator acceptance
- Non-staining formula
- Biodegradable – Friendly to the environment
- Safe formula – Contains no toxic chlorine or sulfur or regulated chemicals
- Vegetable oil base reduces dermatitis
- Made from renewable USA-grown crop-based vegetable oils
- Easy clean-up

INSTALLATION

- Brush on exterior surface to reduce friction.
- Stable for several hours before installation of sheetpile or pilings.

TYPICAL PROPERTIES		<u>Value</u>	<u>Test Method</u>
	Viscosity @40°C, cSt	40	ASTM D445
	Viscosity @100°C, cSt	8.6	ASTM D445
	Viscosity Index	201	ASTM D2270
	Flash Point, °C/°F	326/619	ASTM D92
	Fire Point, °C/°F	358/676	ASTM D92
	Total Sulfur, wt%	0	
	Chlorine, wt%	0	
	Aquatic Toxicity	Non-Toxic	Daphnia
	Biodegradability	Pass	OECD

PACKAGING 55 Gallon Drums
1,2 and 5 Gallon Pails

PRECAUTIONS SOYEASY™ FLUIDS ARE MANUFACTURED FROM HIGH QUALITY NATURAL SEED OILS AND BLENDED WITH SELECT ADDITIVES. AS WITH ALL METALWORKING FLUIDS, GOOD PERSONAL HYGIENE AND CAREFUL HANDLING SHOULD ALWAYS BE PRACTICED. AVOID PROLONGED CONTACT TO SKIN, SPLASHING INTO THE EYES, INGESTION OR INHALING OF VAPOR OR MIST. PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION.

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, ELM MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, ELM RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.

Lee Composites, Inc.
P. O. Box 11286
Spring, Texas 77391-1286

(281)376-6146
Fax: (281)251-8461
Toll-Free: (888)389-4415